-01-269-0872 220



| NSN 5320-01-269-0872 |
|--|
| Pin-rivet - Page 1 of 1 |
| View Online at https://aerobasegroup.com/nsn/5320-01-269-0872 |
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Head Style: |
| Flush countersunk |
| Width Between Flats: |
| Between 0.0947 inches and 0.0967 inches |
| Shank Diameter: |
| Between 0.2490 inches and 0.2495 inches |
| Shank Style: |
| Pin-rivet, straight, threaded |
| Head Major Diameter: |
| 0.3948 inches |
| Grip Length: |
| Between 0.439 inches and 0.500 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Thread Size: |
| 0.250 inches |
| Shear Strength: |
| 95000 single pounds per square inch |
| Countersink Angle: |
| 100.0 degrees |
| Material: |
| Iron alloy 660 |
| Material Specification: |
| Ams 5731 assn standard single material response or ams 5737 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Linf |

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0