
## NSN 5320-01-269-6357

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.933 inches and 0.958 inches

## Head Style:

Flush countersunk

#### Shank Diameter:

0.3690 inches

### Head Major Diameter:

0.537 inches

#### Tip Diameter:

0.3632 inches

#### Lubrication:

Dry film and cetyl alcohol

## Grip Length:

Between 0.427 inches and 0.442 inches

## Thready Qty Per Inch (tpi):

24

## Min. Tensile Strength (psi):

220000 pounds per square inch

## Thread Size:

0.3125 inches

### Shear Strength:

125000 single pounds per square inch

### **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

### Material:

Steel comp xm-13

### **Material Specification:**

Ams 5629 assn standard single material response

### Surface Treatment:

Passivate

## Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

## **Thread Series Designator:**

Unjf

Shelf Life:

N/a

## Unit Of Measure:

---

# NSN 5320-01-269-6357

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

