# NSN 5320-01-269-7555

Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-269-7555

# **Thread Class:**

3b

# **Thread Direction:**

Right-hand

# Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

# Shank Diameter:

Between 0.255 inches and 0.257 inches

#### Shank Style:

Blind rivet, nut and bolt (assembly)

# Head Major Diameter:

0.317 inches

#### **Expansion Device:**

Threaded stem

#### Grip Length:

0.063 mils and 0.125 centimeters

# Thready Qty Per Inch (tpi):

32

# Thread Size:

0.164 inches

# **Countersink Angle:**

Between 98.0 degrees and 102.0 degrees

# **Special Features:**

Furnished w/o bolt

#### Material:

Steel comp 304 sleeve or steel comp 305 sleeve

# **Material Specification:**

Qq-s-763, cond a federal specification all material responses sleeve

# Surface Treatment:

Passivate sleeve

# Surface Treatment Specification:

Qq-p-35 federal specification single treatment response sleeve

#### **Thread Series Designator:**

Unjc

#### Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

No

# Fiig:

A040a0

# NSN 5320-01-269-7555

Blind Rivet - Page 2 of 2

# Mil-std (military Standard):

Mil-s-18732 spec.

