NSN 5320-01-270-4238

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-270-4238 Fastener Length: Between 0.990 inches and 1.010 inches **Head Style:** Undersized oval countersunk **Head Height:** Between 0.004 inches and 0.007 inches **Shank Diameter:** Between 0.166 inches and 0.169 inches **Shank Style:** Straight w/radius chamfered tip **Head Major Diameter:** Between 0.298 inches and 0.303 inches **Head Minor Diameter:** 0.274 mils **Countersink Height:** 0.069 inches **Shear Strength:** 41000 single pounds per square inch **Countersink Angle:** Between 99.5 degrees and 100.5 degrees **Heat Treatment:** T-73 solution heat treated Material: Aluminum alloy 7050 **Material Specification:** Qq-a-430 federal specification single material response **Surface Treatment:**

Anodize or chromate

Surface Treatment Specification:

Mil-a-8625, type 2, cl 1 military specification 1st treatment response or mil-c-5541, cl 1 a or cl 3 military specification 2nd treatment response

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.