

View Online at <https://aerobasegroup.com/nsn/5320-01-270-6734>

Identification Code Color:

Orange and yellow

Fastener Length:

0.326 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.155 inches and 0.159 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

Between 0.282 inches and 0.290 inches

Expansion Device:

Serrated stem-type w

Lubrication:

Dry film

Grip Length:

Between 0.126 inches and 0.187 inches

Features Provided:

Self-locking

Min. Tensile Strength (psi):

375 pounds per square inch

Shear Strength:

620 single pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Heat Treatment:

T-4 solution heat treated sleeve

Material:

Aluminum alloy 2017 sleeve

Material Specification:

Qq-a-430 federal specification all material responses

Surface Treatment:

Anodize sleeve or chromate sleeve

Surface Treatment Specification:

Mil-c-5541 military specification single treatment response stem

Supplementary Features:

Similar to nas1399d5-3 nsn 5320-00-993-7358 except w/ trans lub 20204

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.