NSN 5320-01-270-6734

Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-270-6734

Identification Code Color: Orange and yellow Fastener Length: 0.326 inches Head Style: Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) Shank Diameter: Between 0.155 inches and 0.159 inches Shank Style: Self-plugging mechanically locked stem Head Major Diameter: Between 0.282 inches and 0.290 inches **Expansion Device:** Serrated stem-type w Lubrication: Dry film Grip Length: Between 0.126 inches and 0.187 inches **Features Provided:** Self-locking Min. Tensile Strength (psi): 375 pounds per square inch Shear Strength: 620 single pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Heat Treatment:** T-4 solution heat treated sleeve Material: Aluminum alloy 2017 sleeve **Material Specification:** Qq-a-430 federal specification all material responses **Surface Treatment:** Anodize sleeve or chromate sleeve Surface Treatment Specification: Mil-c-5541 military specification single treatment response stem **Supplementary Features:** Similar to nas1399d5-3 nsn 5320-00-993-7358 except w/ trans lub 20204 Shelf Life: N/a Unit Of Measure:

NSN 5320-01-270-6734

Blind Rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.