## NSN 5320-01-270-6735

Blind Rivet - Page 1 of 2

**Identification Code Color:** 

Orange and yellow Fastener Length:

0.388 inches **Head Style:** 



View Online at https://aerobasegroup.com/nsn/5320-01-270-6735

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:
Between 0.155 inches and 0.159 inches
Shank Style:
Self-plugging mechanically locked stem
Head Major Diameter:
Between 0.282 inches and 0.290 inches
Expansion Device:
Serrated stem-type w
Lubrication:
Dry film
Grip Length:
Between 0.188 inches and 0.250 inches
Features Provided:
Self-locking
Min. Tensile Strength (psi):
375 pounds per square inch
Shear Strength:
710 single pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Heat Treatment:
T-4 solution heat treated sleeve
Material:
Aluminum alloy 7075 stem
Material Specification:
Qq-a-430 federal specification all material responses
Surface Treatment:
Chromate stem
Surface Treatment Specification:
Mil-c-5541 military specification single treatment response stem
Supplementary Features:
Similar to nas1399d5-4 nsn 5320-00-054-8411 except w/ trans lub 20204
Shelf Life:
N/a
Unit Of Measure:

## NSN 5320-01-270-6735

Blind Rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.