NSN 5320-01-270-6736



View Online at https://aerobasegroup.com/nsn/5320-01-270-6736

Blind Rivet - Page 1 of 2 **Identification Code Color:** Orange and yellow Fastener Length: 0.451 inches Head Style: Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) Shank Diameter: Between 0.155 inches and 0.159 inches Shank Style: Self-plugging mechanically locked stem Head Major Diameter: Between 0.282 inches and 0.290 inches **Expansion Device:** Serrated stem-type w Lubrication: Dry film Grip Length: Between 0.251 inches and 0.312 inches **Features Provided:** Self-locking Min. Tensile Strength (psi): 375 pounds per square inch Shear Strength: 755 single pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees

Heat Treatment:

T-4 solution heat treated sleeve

Material:

Aluminum alloy 7075 stem

Material Specification:

Qq-a-430 federal specification all material responses

Surface Treatment:

Chromate stem

Surface Treatment Specification:

Mil-c-5541 military specification single treatment response stem

Supplementary Features:

Similar to nas1399d5-5 nsn 5320-00-928-9908 except w/ trans lub 20204

Shelf Life:

N/a

Unit Of Measure:

NSN 5320-01-270-6736

Blind Rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.

