

View Online at <https://aerobasegroup.com/nsn/5320-01-270-6737>

**Identification Code Color:**

Orange and yellow

**Fastener Length:**

0.513 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.155 inches and 0.159 inches

**Head Major Diameter:**

Between 0.282 inches and 0.290 inches

**Expansion Device:**

Serrated stem-type w

**Lubrication:**

Dry film

**Grip Length:**

Between 0.313 inches and 0.375 inches

**Features Provided:**

Self-locking

**Min. Tensile Strength (psi):**

375 pounds per square inch

**Shear Strength:**

755 single pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Heat Treatment:**

T-4 solution heat treated sleeve

**Material:**

Aluminum alloy 7075 stem

**Material Specification:**

Qq-a-430 federal specification all material responses

**Surface Treatment:**

Chromate stem

**Surface Treatment Specification:**

Mil-c-5541 military specification single treatment response stem

**Supplementary Features:**

Similar to nas1399d5-6 nsn 5320-00-993-7358 except w/ trans lub 20204

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0

**Mil-std (military Standard):**

Mil-a-8625 spec.