NSN 5320-01-270-6737

Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-270-6737

Identification Code Color:

Orange and yellow

Fastener Length:

0.513 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.155 inches and 0.159 inches

Head Major Diameter:

Between 0.282 inches and 0.290 inches

Expansion Device:

Serrated stem-type w

Lubrication:

Dry film

Grip Length:

Between 0.313 inches and 0.375 inches

Features Provided:

Self-locking

Min. Tensile Strength (psi):

375 pounds per square inch

Shear Strength:

755 single pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Heat Treatment:

T-4 solution heat treated sleeve

Material:

Aluminum alloy 7075 stem

Material Specification:

Qq-a-430 federal specification all material responses

Surface Treatment:

Chromate stem

Surface Treatment Specification:

Mil-c-5541 military specification single treatment response stem

Supplementary Features:

Similar to nas1399d5-6 nsn 5320-00-993-7358 except w/ trans lub 20204

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5320-01-270-6737

Blind Rivet - Page 2 of 2

Fiig: A040a0

Mil-std (military Standard):

Mil-a-8625 spec.

