Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-270-6738

Identification Code Color:

Orange and yellow

Fastener Length:

0.576 inches

Head Style:

Universal

Head Height:

Between 0.067 inches and 0.077 inches

Shank Diameter:

Between 0.155 inches and 0.159 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

Between 0.296 inches and 0.328 inches

Expansion Device:

Serrated stem-type w

Lubrication:

Dry film

Grip Length:

Between 0.376 inches and 0.437 inches

Features Provided:

Self-locking

Min. Tensile Strength (psi):

375 pounds per square inch

Shear Strength:

755 single pounds per square inch

Heat Treatment:

T-4 solution heat treated sleeve

Material:

Aluminum alloy 2017 sleeve

Material Specification:

Qq-a-430 federal specification all material responses

Surface Treatment:

Anodize sleeve or chromate sleeve

Surface Treatment Specification:

Mil-c-5541 military specification single treatment response stem

Supplementary Features:

Similar to nas1398d5-7 nsn 5320-00-267-9588 except w/ trans lub 20204

Shelf Life:

N/a

Unit Of Measure:

NSN 5320-01-270-6738

Blind Rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.

