

View Online at <https://aerobasegroup.com/nsn/5320-01-270-8184>

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.2580 inches and 0.2600 inches

Head Major Diameter:

Between 0.3898 inches and 0.3948 inches

Expansion Device:

Serrated stem-type w

Grip Length:

Between 0.345 inches and 0.406 inches

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 4130 bolt or steel comp 8740 boltsteel comp 4130 nut or steel comp 8740 nutsteel comp 303 sleeve or steel comp 304 sleeve or steel comp 303se sleeve

Material Specification:

Mil-s-6758 military specification 1st material response bolt or mil-s-6049 military specification 2nd material response boltmil-s-6758 military specification 1st material response nut or mil-s-6049 military specification 2nd material response nutqq-s-763 federal specification 1st material response sleeve or qq-s-763 federal specification 2nd material response sleeve or ams 5639 assn standard 2nd material response sleeve or ams 5641 assn standard 3rd material response sleeve

Surface Treatment:

Cadmium bolt and chromate boltcadmium nut and chromate nutpassivate sleeve and cadmium sleeve

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response boltqq-p-416, type 2, cl 2 federal specification single treatment response nutmil-s-5002 military specification 1st treatment response sleeve and qq-p-416, type 1, cl 3 federal specification 2nd treatment response sleeve

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-6758 spec.