# NSN 5320-01-272-3352

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-272-3352



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.988 inches and 1.008 inches

## Head Style:

Flush countersunk

#### Width Between Flats:

Between 0.0791 inches and 0.0806 inches

#### Shank Diameter:

Between 0.2095 inches and 0.2100 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

0.3016 inches

#### Lubrication:

Solid film and cetyl alcohol or dry film

#### Grip Length:

Between 0.438 inches and 0.448 inches

## Thready Qty Per Inch (tpi):

32

## **Thread Size:**

0.190 inches

## Shear Strength:

95000 single pounds per square inch

#### **Countersink Angle:**

100.0 degrees

## Material:

Titanium alloy uns r56400

#### **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### Surface Treatment:

Anodize

## **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# NSN 5320-01-272-3352

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

