NSN 5320-01-275-1999



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-275-1999 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.083 inches and 1.108 inches **Head Style:** Flush countersunk **Shank Diameter:** 0.3547 inches **Head Major Diameter:** 0.522 inches **Tip Diameter:** 0.3436 inches Lubrication: Dry film and cetyl alcohol **Grip Length:** Between 0.677 inches and 0.692 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 220000 pounds per square inch Thread Size: 0.312 inches **Shear Strength:** 1250000 single pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Special Features:** 8-32unjc-3b thread size, 0.280 in. Lg along the longitudinal axis from the head end. 0.120 in. Slot lg. 0.060 in. Slot w located 0.220 in. From top of head to center of slot Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate**

Shelf Life: N/a

Unjc

Surface Treatment Specification:

Thread Series Designator:

Qq-p-35 federal specification single treatment response

NSN 5320-01-275-1999

Pin-rivet - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A528u0