# NSN 5320-01-276-4924

Pin-rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-276-4924

## Head Style:

Flush countersunk

## Shank Diameter:

Between 0.1880 inches and 0.1895 inches

## Shank Style:

Pin-rivet, multiple grooved

## Head Major Diameter:

0.305 inches

Lubrication:

Cetyl alcohol

#### Grip Length:

Between 0.689 inches and 0.750 inches

#### **Features Provided:**

Sealant vent groove

## Min. Tensile Strength (psi):

160000 pounds per square inch

## Hardness Rating:

77.0 rockwell superficial 15-n and 82.0 rockwell superficial 15-n

## **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

## Material:

Steel comp 8740 or steel comp 4340 or steel comp 4140

## Material Specification:

Astm a547 assn standard all material responses

## Surface Treatment:

Cadmium and chromate

## Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

## **Specification Data:**

80205-nas1436 professional/industrial association standard

#### Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

## Fiig:

A528u0