## NSN 5320-01-278-5828



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-278-5828 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.348 inches and 1.388 inches **Head Style:** Err-090 **Head Height:** Between 0.042 inches and 0.050 inches Width Between Flats: Between 0.079 inches and 0.081 inches **Shank Diameter:** Between 0.202 inches and 0.203 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.298 inches and 0.312 inches **Grip Length:** Between 1.001 inches and 1.062 inches **Thread Size:** 0.190 inches **Shear Strength:** 108000 single pounds per square inch **Special Features:** Ov size pt u/o repair work Material: Steel comp 4340 or steel comp 8740 **Material Specification:** Aisi uns s43400 assn standard 1st material response or aisi uns s87400 assn standard 2nd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification all treatment responses **Thread Series Designator:** Unjf **Specification Data:** 80205-nas4450 professional/industrial association standard Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5320-01-278-5828

Pin-rivet - Page 2 of 2



Demi			

No

Fiig:

A528u0