NSN 5320-01-279-0505



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-279-0505 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.052 inches and 1.072 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.1270 inches and 0.1295 inches **Shank Diameter:** Between 0.3427 inches and 0.3432 inches **Shank Style: Head Major Diameter:** Between 0.5001 inches and 0.5051 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.557 inches and 0.567 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.312 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 100.0 degrees **Special Features:** Color code black on thread end Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** 294, cagec 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5320-01-279-0505

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0