NSN 5320-01-279-3384

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-279-3384

| Head Style: |
|---|
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) |
| Shank Diameter: |
| Between 0.2580 inches and 0.2600 inches |
| Shank Style: |
| Threaded self-plugging shank w/sleeve |
| Head Major Diameter: |
| 0.375 inches |
| Expansion Device: |
| Threaded stem |
| Lubrication: |
| Dry film or cetyl alcohol or paraffin wax |
| Grip Length: |
| 0.313 inches |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Material: |
| Titanium alloy uns r56400 stem |
| Material Specification: |
| Qq-s-763 federal specification 1st material response sleeve or ams5639 assn standard 2nd material response sleeve or ams5641 assn |
| standard 3rd material response sleeve |
| Surface Treatment: |
| Passivate sleeve |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response sleeve |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A040a0 |