

View Online at <https://aerobasegroup.com/nsn/5320-01-279-9153>

**Head Style:**

Universal

**Shank Diameter:**

Between 0.340 inches and 0.342 inches

**Shank Style:**

Blind rivet, nut and bolt (assembly)

**Head Major Diameter:**

0.442 inches

**Expansion Device:**

Threaded sleeve

**Lubrication:**

Carbo wax or cetyl alcohol or dry film

**Grip Length:**

Between 0.532 inches and 0.594 inches

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c nut and 43.0 rockwell c nut

**Material:**

Steel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nut

**Material Specification:**

Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 2nd material response sleeve or ams 5641 assn standard 3rd material response sleeve

**Surface Treatment:**

Passivate sleeve and cadmium sleeve

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification 1st treatment response nut or nas 672 assn standard 2nd treatment response nut and qq-p-416 federal specification 3rd treatment response nut

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0

**Mil-std (military Standard):**

Mil-s-6758 spec.