

View Online at <https://aerobasegroup.com/nsn/5320-01-279-9153>

Head Style:

Universal

Shank Diameter:

Between 0.340 inches and 0.342 inches

Shank Style:

Blind rivet, nut and bolt (assembly)

Head Major Diameter:

0.442 inches

Expansion Device:

Threaded sleeve

Lubrication:

Carbo wax or cetyl alcohol or dry film

Grip Length:

Between 0.532 inches and 0.594 inches

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c nut and 43.0 rockwell c nut

Material:

Steel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nut

Material Specification:

Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 2nd material response sleeve or ams 5641 assn standard 3rd material response sleeve

Surface Treatment:

Passivate sleeve and cadmium sleeve

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification 1st treatment response nut or nas 672 assn standard 2nd treatment response nut and qq-p-416 federal specification 3rd treatment response nut

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0

Mil-std (military Standard):

Mil-s-6758 spec.