
# NSN 5320-01-280-5902

Pin-rivet - Page 1 of 2





## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.678 inches and 1.698 inches

#### Head Style:

Flush countersunk

### Width Between Flats:

Between 0.1270 inches and 0.1295 inches

## Shank Diameter:

Between 0.3266 inches and 0.3276 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.4689 inches and 0.4739 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

## Grip Length:

1.193 inches

## Thready Qty Per Inch (tpi):

24

## Thread Size:

0.312 inches

#### **Countersink Angle:**

100.0 degrees

#### **Special Features:**

Color code black on thread end

## Material:

Titanium alloy uns r56400

## **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### Surface Treatment:

Aluminum alloy

#### **Surface Treatment Specification:**

294, cagec 73197 mfr ref single treatment response

## **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

## Unit Of Measure:

--

# NSN 5320-01-280-5902

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

