NSN 5320-01-281-0581

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-281-0581 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.825 inches and 1.850 inches **Head Style:** Err-090 **Head Height:** Between 0.144 inches and 0.156 inches **Shank Diameter:** 0.6046 inches **Head Major Diameter:** Between 0.853 inches and 0.869 inches **Tip Diameter:** 0.5807 inches Lubrication: Cetyl alcohol **Grip Length:** Between 1.240 inches and 1.255 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 180000 pounds per square inch **Thread Size:** 0.500 inches **Shear Strength:** 108000 single pounds per square inch Material: Steel comp 8740 or steel comp e4340 **Material Specification:** Mil-s-6049 military specification 1st material response or mil-s-5000 military specification 2nd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5320-01-281-0581

Pin-rivet - Page 2 of 2



_										
וו	0	m	ш	м	•	iza	31	^	n	

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.