# NSN 5320-01-281-3421

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-281-3421



# Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 1.552 inches and 1.572 inches

#### Head Style:

Flush countersunk

#### Width Between Flats:

Between 0.1270 inches and 0.1295 inches

#### Shank Diameter:

Between 0.3266 inches and 0.3276 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

0.4739 inches

# Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

# Grip Length:

1.062 inches

Thready Qty Per Inch (tpi):

24

# Thread Size:

0.312 inches

#### Shear Strength:

95000 single pounds per square inch

# **Countersink Angle:**

100.0 degrees

# **Special Features:**

Color code black on thread end

# Material:

Titanium alloy uns r56400

# **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

# Surface Treatment:

Aluminum

# Surface Treatment Specification:

294, cagec 73197 mfr ref single treatment response

# Thread Series Designator:

Unjf

# Shelf Life:

N/a

# NSN 5320-01-281-3421

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

