NSN 5320-01-281-7831

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-281-7831

Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 1.260 inches and 1.280 inches
Head Style:
Err-090
Head Height:
Between 0.077 inches and 0.090 inches
Width Between Flats:
Between 0.0947 inches and 0.0967 inches
Shank Diameter:
Between 0.2485 inches and 0.2495 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.415 inches and 0.440 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
Grip Length:
0.880 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Thread Size:
0.250 inches
Shear Strength:
95000 single pounds per square inch
Special Features:
Color code green on thread end
Material:
Iron alloy 660
Material Specification:
Ams 5737 assn standard single material response or ams 5731 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification single treatment response
Thread Series Designator:
Unjf

NSN 5320-01-281-7831

Pin-rivet - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0