## NSN 5320-01-281-9215

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-281-9215 **Thread Class:** За **Thread Direction:** Right-hand **Fastener Length:** Between 1.590 inches and 1.715 inches **Head Style:** Flush countersunk **Shank Diameter:** Between 0.2005 inches and 0.2025 inches **Shank Style:** Pin-rivet, multiple grooved **Head Major Diameter:** 0.386 inches **Grip Length:** Between 0.751 inches and 0.812 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 180000 pounds per square inch **Thread Size:** 0.164 inches **Shear Strength:** 108000 single pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp 8740 **Material Specification:** Aisi 8740 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification all treatment responses **Thread Series Designator:** Uns Shelf Life: **Unit Of Measure:** 

Shelf Life:
N/a
Unit Of Measure:
-Demilitarization:
No

## NSN 5320-01-281-9215

Pin-rivet - Page 2 of 2



Fiig:

A528u0