# NSN 5320-01-281-9215

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-281-9215



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.590 inches and 1.715 inches

#### Head Style:

Flush countersunk

#### Shank Diameter:

Between 0.2005 inches and 0.2025 inches

## Shank Style:

Pin-rivet, multiple grooved

#### Head Major Diameter:

0.386 inches

## Grip Length:

Between 0.751 inches and 0.812 inches

#### Thready Qty Per Inch (tpi):

56

## Min. Tensile Strength (psi):

180000 pounds per square inch

## Thread Size:

0.164 inches

## Shear Strength:

108000 single pounds per square inch

#### **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

#### Material:

Steel comp 8740

#### **Material Specification:**

Aisi 8740 assn standard single material response

#### Surface Treatment:

Cadmium and chromate

#### Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification all treatment responses

### **Thread Series Designator:**

Uns

## Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5320-01-281-9215

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

