## NSN 5320-01-283-2457

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-283-2457

Fastener Length:
Between 0.088 inches and 0.098 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Hole Diameter:
Between 0.028 inches and 0.038 inches
Shank Diameter:
Between 0.058 inches and 0.061 inches
Shank Style:
Tubular
Head Major Diameter:
0.106 inches
Hole Depth:
Between 0.040 inches and 0.050 inches
Countersink Angle:
90.0 degrees
Material:
Copper alloy 210 or copper alloy 220 or copper alloy 230 or copper alloy 240 or copper alloy 260 or copper alloy 270 or copper alloy 27
or copper alloy 510 or copper alloy 745 or copper alloy 752 or copper alloy 764 or copper alloy 770
Material Specification:
Qq-w-321 federal specification all material responses
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification all treatment responses
Shelf Life:
N/a
Unit Of Measure:
<del>-</del>
Demilitarization:
No
Fiig:
A040a0