

View Online at <https://aerobasegroup.com/nsn/5320-01-283-4695>

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.274 inches and 0.276 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Head Major Diameter:

0.472 inches

Expansion Device:

Threaded stem

Grip Length:

0.094 mils and 0.156 centimeters

Features Provided:

Self-locking

Hardness Rating:

39.0 rockwell c bolt and 43.0 rockwell c bolt

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 4140 bolt or steel comp 8740 bolt or steel comp 4130 bolt

Material Specification:

Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 2nd material response sleeve or ams 5641 assn standard 3rd material response sleeve

Surface Treatment:

Cadmium sleeve

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification all treatment responses bolt

Specification Data:

80205-nas1754 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0

Mil-std (military Standard):

Mil-s-5626 spec.