NSN 5320-01-283-6479

Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-283-6479

| Thread Class: |
|--|
| 3b |
| Head Style: |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) |
| Shank Diameter: |
| Between 0.527 inches and 0.530 inches |
| Shank Style: |
| Blind rivet, nut and bolt (assembly) |
| Head Major Diameter: |
| 0.590 inches |
| Expansion Device: |
| Expander |
| Grip Length: |
| Between 0.437 inches and 0.500 inches |
| Features Provided: |
| Self-locking |
| Thready Qty Per Inch (tpi): |
| 24 |
| Thread Size: |
| 0.375 inches |
| Shear Strength: |
| 125000 single pounds per square inch |
| Countersink Angle: |
| 100.0 degrees |
| Special Features: |
| Furnished w/o bolt |
| Material: |
| Steel comp 304 sleeve or steel comp 305 sleeve |
| Material Specification: |
| Qq-s-763 federal specification all material responses sleeve |
| Surface Treatment: |
| Passivate sleeve |
| Surface Treatment Specification: |
| Qq-p-416, type 2, cl 2 federal specification all treatment responses expander |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5320-01-283-6479

Blind Rivet - Page 2 of 2



Fiig:

A040a0