## NSN 5320-01-284-1454

Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-284-1454
Thread Class:
3b
Thread Direction:
Right-hand
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.309 inches and 0.312 inches
Shank Style:
Blind rivet, nut and bolt (assembly)
Head Major Diameter:
0.372 inches
Expansion Device:
Expander
Lubrication:
Solid film
Grip Length:
0.250 mils and 0.312 centimeters
Thready Qty Per Inch (tpi):
32
Thread Size:
0.190 inches
Countersink Angle:
Between 98.0 degrees and 102.0 degrees
Special Features:
Furnished w/o bolt
Material:
Steel comp 304 sleeve or steel comp 305 sleeve or steel comp xm-7 sleeve
Material Specification:
Qq-s-763 federal specification 1st material response sleeve or qq-s-763 federal specification 2nd material response sleeve or astm a493
assn standard 3rd material response sleeve
Surface Treatment:
Passivate sleeve
Surface Treatment Specification:
Qq-p-35, type 1 federal specification single treatment response sleeve
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:

No

## **NSN 5320-01-284-1454**Blind Rivet - Page 2 of 2



Fiig:

A040a0