## NSN 5320-01-284-1455



Blind Rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-284-1455 **Thread Class:** 3b **Thread Direction:** Right-hand **Head Style:** Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) **Shank Diameter:** Between 0.387 inches and 0.390 inches **Shank Style:** Blind rivet, nut and bolt (assembly) **Head Major Diameter:** 0.450 inches **Expansion Device:** Expander Lubrication: Solid film **Grip Length:** 0.250 mils and 0.312 centimeters Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Countersink Angle:** Between 98.0 degrees and 102.0 degrees **Special Features:** Furnished w/o bolt Material: Steel comp 304 sleeve or steel comp 305 sleeve or steel comp xm-7 sleeve **Material Specification:** Qq-s-763 federal specification 1st material response sleeve or qq-s-763 federal specification 2nd material response sleeve or astm a493 assn standard 3rd material response sleeve **Surface Treatment:** Passivate sleeve **Surface Treatment Specification:** Qq-p-35, type 1 federal specification single treatment response sleeve **Thread Series Designator:** Unjf Shelf Life: N/a

No

**Unit Of Measure:** 

Demilitarization:

## **NSN 5320-01-284-1455**Blind Rivet - Page 2 of 2



Fiig:

A040a0