NSN 5320-01-284-8684

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-284-8684 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.180 inches and 1.200 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.190 inches and 0.193 inches **Shank Diameter:** Between 0.451 inches and 0.453 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.662 inches and 0.668 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.495 inches and 0.510 inches Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.438 inches **Shear Strength:** 30600 double pounds per square inch **Countersink Angle:** 100.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard 1st material response or ams4967 assn standard 2nd material response **Thread Series Designator:** Unjf **Specification Data:** 73197-hlt109 manufacturers standard Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5320-01-284-8684

Pin-rivet - Page 2 of 2



Fiig:

A528u0