## NSN 5320-01-284-8685

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-284-8685 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.480 inches and 1.500 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.221 inches and 0.224 inches **Shank Diameter:** Between 0.488 inches and 0.493 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.748 inches and 0.754 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.745 inches and 0.760 inches Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.500 inches **Shear Strength:** 39600 double pounds per square inch **Countersink Angle:** 100.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard 1st material response or ams4967 assn standard 2nd material response **Thread Series Designator:** Unjf **Specification Data:** 73197-hlt109 manufacturers standard Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5320-01-284-8685

Pin-rivet - Page 2 of 2



Fiig:

A528u0