NSN 5320-01-285-9221

Solid Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-285-9221 Fastener Length: Between 0.552 inches and 0.572 inches **Head Style:** Undersized oval countersunk **Head Height:** Between 0.003 inches and 0.005 inches **Shank Diameter:** Between 0.155 inches and 0.158 inches **Shank Style:** Straight w/radius chamfered tip **Head Major Diameter:** 0.2469 inches **Head Minor Diameter:** 0.185 mils and 0.195 centimeters **Countersink Height:** 0.0372 inches **Shear Strength:** 32000 single pounds per square inch **Countersink Angle:** Between 99.5 degrees and 100.5 degrees **Special Features:** Optional squared end **Heat Treatment:** T-81 solution heat treated Material: Aluminum alloy 2219 **Material Specification:** Qq-a-430 federal specification single material response **Surface Treatment:** Anodize or chromate **Surface Treatment Specification:** Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response **Specification Data:** 80205-nas1097 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig:

A040a0

NSN 5320-01-285-9221

Solid Rivet - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.