## NSN 5320-01-285-9227

Solid Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-285-9227

## Fastener Length:

Between 0.490 inches and 0.510 inches

## Head Style:

Undersized oval countersunk

## Head Height:

Between 0.003 inches and 0.005 inches

## Shank Diameter:

Between 0.155 inches and 0.158 inches

#### Shank Style:

Straight w/radius chamfered tip

#### Head Major Diameter:

0.2469 inches

#### Head Minor Diameter:

0.185 mils and 0.195 centimeters

## **Countersink Height:**

0.0372 inches

## Shear Strength:

32000 single pounds per square inch

## **Countersink Angle:**

Between 99.5 degrees and 100.5 degrees

## **Special Features:**

Optional squared end

## Heat Treatment:

T-81 solution heat treated

## Material:

Aluminum alloy 2219

## **Material Specification:**

Qq-a-430 federal specification single material response

## Surface Treatment:

Anodize or chromate

## Surface Treatment Specification:

Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response

## **Specification Data:**

80205-nas1097 professional/industrial association standard

## Shelf Life:

N/a

## Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A040a0

# NSN 5320-01-285-9227

Solid Rivet - Page 2 of 2

## Mil-std (military Standard):

Mil-a-8625 spec.

