
# NSN 5320-01-286-9197

Pin-rivet - Page 1 of 2





# Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.052 inches and 1.072 inches

#### Head Style:

Flush countersunk

#### Width Between Flats:

Between 0.0635 inches and 0.0645 inches

#### Shank Diameter:

Between 0.1630 inches and 0.1635 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

0.3304 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

## Grip Length:

0.755 inches

# Thready Qty Per Inch (tpi):

32

## Min. Tensile Strength (psi):

160000 pounds per square inch

## Thread Size:

0.164 inches

## Shear Strength:

95000 single pounds per square inch

#### Countersink Angle:

100.0 degrees

#### Material:

Titanium alloy uns r56400

#### Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### Thread Series Designator:

Unjc

## Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# NSN 5320-01-286-9197

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

