NSN 5320-01-287-0389

Solid Rivet - Page 1 of 1

Mil-a-8625 spec.



View Online at https://aerobasegroup.com/nsn/5320-01-287-0389

view Offiline at https://defobasegroup.com/hsh/0520-01-207-0505
Fastener Length:
Between 0.178 inches and 0.198 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.108 inches and 0.112 inches
Shank Style:
Straight w/radius chamfered tip
Head Major Diameter:
Between 0.175 inches and 0.183 inches
Shear Strength:
26000 single pounds per square inch
Countersink Angle:
Between 99.5 degrees and 100.5 degrees
Heat Treatment:
T-4 solution heat treated
Material:
Aluminum alloy 2117
Material Specification:
Qq-a-430 federal specification single material response
Surface Treatment:
Chromate or anodize
Surface Treatment Specification:
Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response
Specification Data:
80205-nas1241 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):