NSN 5320-01-287-6053

Solid Rivet - Page 1 of 1

A040a0

Mil-std (military Standard):

Mil-t-10727 spec.



View Online at https://aerobasegroup.com/nsn/5320-01-287-6053 **Fastener Length:** Between 0.271 inches and 0.291 inches **Head Style:** Flat/tinner's **Head Height:** Between 0.055 inches and 0.069 inches **Shank Diameter:** Between 0.144 inches and 0.150 inches **Shank Style:** Straight **Head Major Diameter:** Between 0.289 inches and 0.311 inches Min. Tensile Strength (psi): 43000 pounds per square inch **Shear Strength:** 32000 single pounds per square inch **Heat Treatment:** Annealed Material: Steel comp 1005 or steel comp 1022 **Material Specification:** Sae j430, grade 0 assn standard all material responses or 66, uns g10050 through g10220 federal standard all material responses **Surface Treatment:** Tin **Surface Treatment Specification:** Mil-t-10727 military specification single treatment response **Specification Data:** 96906-ms51931 government standard and 24617-114904 manufacturers standard and 80204-ansi b18.1.1 professional/industrial association standard and 81343-j492 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: