## NSN 5320-01-287-7614

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-287-7614 **Thread Class:** За **Thread Direction:** Right-hand **Identification Code Color:** Blue **Fastener Length:** Between 0.927 inches and 0.947 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0635 inches and 0.0645 inches **Shank Diameter:** Between 0.1625 inches and 0.1635 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.2564 inches and 0.2612 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 0.625 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.164 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Hi-shear specification 306 type 1 mfr ref single treatment response **Thread Series Designator:** Unjc

N/a

Shelf Life:

## NSN 5320-01-287-7614

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0