# NSN 5320-01-288-6073

Pin-rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-288-6073

# Thread Direction:

Right-hand

### Fastener Length:

Between 18.5 millimeters and 19.0 millimeters

#### Head Style:

Flush countersunk

#### Width Between Flats:

Between 2.4 millimeters and 2.5 millimeters

#### Shank Diameter:

Between 6.97 millimeters and 6.99 millimeters

Shank Style:

#### Head Major Diameter:

Between 10.5 millimeters and 10.6 millimeters

#### Grip Length:

Between 6.9 millimeters and 7.1 millimeters

#### **Thread Size:**

7.0 millimeters

#### **Thread Pitch In Millimeters:**

0.65

#### Shear Strength:

50400 double newtons per square millimeter

#### **Countersink Angle:**

100.0 degrees

#### **Thread Tolerance Class:**

4h external

#### Material:

Titanium alloy uns r56400

#### Material Specification:

Ams4967 assn standard single material response

#### **Thread Series Designator:**

lso m

## **Specification Data:**

73197-hl-611-06-7 manufacturers standard

## Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A528u0