NSN 5320-01-288-6629

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-288-6629

Fastener Length:
Between 0.333 inches and 0.353 inches
Head Style:
Countersunk w/ reverse chamfer
Head Height:
0.035 inches
Shank Diameter:
Between 0.155 inches and 0.158 inches
Shank Style:
Straight w/radius chamfered tip
Head Major Diameter:
0.210 inches
Min. Tensile Strength (psi):
38000 pounds per square inch
Minimum Yield Strength:
18000 pounds per square inch
Shear Strength:
26000 single pounds per square inch
Countersink Angle:
Between 118.5 degrees and 121.5 degrees
Heat Treatment:
T-4 solution heat treated
T-4 solution heat treated
T-4 solution heat treated Material:
T-4 solution heat treated Material: Aluminum alloy 2117
T-4 solution heat treated Material: Aluminum alloy 2117 Material Specification:
T-4 solution heat treated Material: Aluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response
T-4 solution heat treated Material: Aluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response Surface Treatment:
T-4 solution heat treated Material: Aluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Anodize
T-4 solution heat treated Material: Aluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification:
T-4 solution heat treated Material: Aluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2, cl 1 military specification single treatment response
T-4 solution heat treated Material: Aluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2, cl 1 military specification single treatment response Shelf Life:
T-4 solution heat treated Material: Aluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2, cl 1 military specification single treatment response Shelf Life: N/a
T-4 solution heat treated Material: Aluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2, cl 1 military specification single treatment response Shelf Life: N/a
T-4 solution heat treated Material: Aluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2, cl 1 military specification single treatment response Shelf Life: N/a Unit Of Measure:
T-4 solution heat treated Material: Aluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2, cl 1 military specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization:
T-4 solution heat treated Material: Aluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2, cl 1 military specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No
T-4 solution heat treated Material: Aluminum alloy 2117 Material Specification: Qq-a-430 federal specification single material response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625, type 2, cl 1 military specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: