

View Online at <https://aerobasegroup.com/nsn/5320-01-288-6632>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.947 inches and 0.972 inches

**Head Style:**

Flush countersunk

**Shank Diameter:**

0.2624 inches

**Shank Style:**

Pin-riquet, tapered, threaded

**Head Major Diameter:**

0.413 inches

**Tip Diameter:**

0.2525 inches

**Lubrication:**

Dry film and cetyl alcohol

**Grip Length:**

Between 0.615 inches and 0.630 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

260000 pounds per square inch

**Thread Size:**

0.250 inches

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel comp h11

**Material Specification:**

Ams 6487 assn standard single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Mil-c-8837, type 2 military specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1724 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-c-8837 spec.