

View Online at <https://aerobasegroup.com/nsn/5320-01-288-6636>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.322 inches and 1.347 inches

Head Style:

Flush countersunk

Shank Diameter:

0.2754 inches

Shank Style:

Pin-riquet, tapered, threaded

Head Major Diameter:

0.426 inches

Tip Diameter:

0.2577 inches

Lubrication:

Dry film and cetyl alcohol

Grip Length:

Between 0.990 inches and 1.005 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

260000 pounds per square inch

Thread Size:

0.250 inches

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp h11

Material Specification:

Ams 6487 assn standard single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Mil-c-8837, type 2 military specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas1724 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-c-8837 spec.