# NSN 5320-01-288-9206

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-288-9206



# **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 1.534 inches and 1.574 inches

#### Head Style:

Flush countersunk

#### Width Between Flats:

Between 0.1582 inches and 0.1617 inches

### Shank Diameter:

Between 0.3891 inches and 0.3901 inches

#### Shank Style:

Pin-rivet, straight, threaded

### Head Major Diameter:

#### 0.588 inches

Lubrication:

Dry film

# Grip Length:

Between 1.001 inches and 1.062 inches

## Thready Qty Per Inch (tpi):

24

## Thread Size:

0.375 inches

#### Shear Strength:

156000 single pounds per square inch

#### **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

## **Special Features:**

Mechanical lock feature on threads

#### Material:

Steel comp h11

## Material Specification:

Ams 6485 assn standard single material response or ams 6487 assn standard single material response

#### Surface Treatment:

Cadmium and nickel

# Surface Treatment Specification:

Ams 2416 assn standard single treatment response

# Thread Series Designator:

Unjf

# Shelf Life:

N/a

# NSN 5320-01-288-9206

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

