NSN 5320-01-288-9440



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-288-9440 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.221 inches and 1.261 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.1582 inches and 0.1617 inches **Shank Diameter:** Between 0.3891 inches and 0.3901 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.588 inches Lubrication: Dry film **Grip Length:** Between 0.689 inches and 0.750 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.375 inches **Shear Strength:** 156000 single pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Special Features:** Mechanical lock feature on threads Material: Steel comp h11 **Material Specification:** Ams 6485 assn standard single material response or ams 6487 assn standard single material response **Surface Treatment:** Cadmium and nickel **Surface Treatment Specification:** Ams 2416 assn standard single treatment response **Thread Series Designator:** Unjf

N/a

Shelf Life:

NSN 5320-01-288-9440

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0