

View Online at <https://aerobasegroup.com/nsn/5320-01-288-9441>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.284 inches and 1.324 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.1582 inches and 0.1617 inches

**Shank Diameter:**

Between 0.3891 inches and 0.3901 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

0.588 inches

**Lubrication:**

Dry film

**Grip Length:**

Between 0.751 inches and 0.812 inches

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.375 inches

**Shear Strength:**

156000 single pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Special Features:**

Mechanical lock feature on threads

**Material:**

Steel comp h11

**Material Specification:**

Ams 6485 assn standard single material response or ams 6487 assn standard single material response

**Surface Treatment:**

Cadmium and nickel

**Surface Treatment Specification:**

Ams 2416 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0