NSN 5320-01-289-6173Blind Rivet - Page 1 of 1



| /iew Online at https://aerobasegroup.com/nsn/5320-01-289-6173 |
|-------------------------------------------------------------------------------------------------------------------------------------------------|
| Shank Diameter: |
| Between 0.2740 inches and 0.2760 inches |
| Head Major Diameter: |
| 0.463 inches |
| Features Provided: |
| Drive nut |
| Hardness Rating: |
| 39.0 rockwell c nut and 43.0 rockwell c nut |
| Material: |
| Steel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nut |
| Material Specification: |
| Mil-s-6758 military specification 1st material response nut or mil-s-5626 military specification 2nd material response nut or mil-s-6049 milita |
| specification 3rd material response nut |
| Surface Treatment: |
| Passivate sleeve and cadmium sleeve |
| Surface Treatment Specification: |
| Qq-p-416, type 2, cl 2 federal specification single treatment response nut |
| Specification Data: |
| 30205-nas1750 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Jnit Of Measure: |
| - |
| Demilitarization: |
| No |
| Fiig: |
| A040a0 |
| Mil-std (military Standard): |
| Mil-s-6758 spec. |
| |
| |
| |
| |
| |