NSN 5320-01-290-0093

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-290-0093

Fastener Length:
Between 0.193 inches and 0.213 inches
Head Style:
Flat/tinner's
Head Height:
Between 0.028 inches and 0.040 inches
Shank Diameter:
Between 0.107 inches and 0.113 inches
Shank Style:
Straight
Head Major Diameter:
Between 0.265 inches and 0.285 inches
Min. Tensile Strength (psi):
43000 pounds per square inch
Shear Strength:
32000 single pounds per square inch
Heat Treatment:
Annealed
Material:
Steel comp 1005 or steel comp 1022
Material Specification:
Ase j430, grade 0 assn standard all material responses or 66, uns g10050 through g10220 federal standard all material responses
Surface Treatment:
Tin
Surface Treatment Specification:
Mil-t-10727 military specification single treatment response
Specification Data:
96906-ms51931 government standard and 24617-140134 manufacturers standard and 80204-ansi b18.1.1 professional/industrial
association standard and 81343-j492 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A040a0

Mil-std (military Standard):

Mil-t-10727 spec.