# NSN 5320-01-290-0093

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-290-0093

# Fastener Length:

Between 0.193 inches and 0.213 inches

#### Head Style:

Flat/tinner's

# Head Height:

Between 0.028 inches and 0.040 inches

## Shank Diameter:

Between 0.107 inches and 0.113 inches

#### Shank Style:

Straight

#### Head Major Diameter:

Between 0.265 inches and 0.285 inches

#### Min. Tensile Strength (psi):

43000 pounds per square inch

#### Shear Strength:

32000 single pounds per square inch

Heat Treatment:

Annealed

## Material:

Steel comp 1005 or steel comp 1022

#### Material Specification:

Ase j430, grade 0 assn standard all material responses or 66, uns g10050 through g10220 federal standard all material responses

#### Surface Treatment:

Tin

#### Surface Treatment Specification:

Mil-t-10727 military specification single treatment response

#### **Specification Data:**

96906-ms51931 government standard and 24617-140134 manufacturers standard and 80204-ansi b18.1.1 professional/industrial

association standard and 81343-j492 professional/industrial association standard

#### Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

# Fiig:

A040a0

#### Mil-std (military Standard):

Mil-t-10727 spec.