NSN 5320-01-290-5517

Pin-rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-290-5517

Thread Direction:	
Right-hand	
Fastener Length:	
Between 40.5 millimeters and 41.0 millimeters	
Head Style:	
Flush countersunk	
Width Between Flats:	
Between 2.4 millimeters and 2.5 millimeters	
Shank Diameter:	
Between 6.97 millimeters and 6.99 millimeters	
Shank Style:	
Pin-rivet, straight, threaded	
Head Major Diameter:	
Between 10.5 millimeters and 10.6 millimeters	
Grip Length:	
Between 28.9 millimeters and 29.1 millimeters	
Thread Size:	
7.0 millimeters	
Thread Pitch In Millimeters:	
0.65	
Shear Strength:	
50400 double newtons per square millimeter	
Countersink Angle:	
100.0 degrees	
Thread Tolerance Class:	
4h external	
Material:	
Titanium alloy uns r56400	
Material Specification:	
Ams4967 assn standard single material response	
Thread Series Designator:	
lso m	
Specification Data:	
73197-hl-611-06-29 manufacturers standard	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A528u0	